

What Is Claimed Is:

1. An electric wax chisel comprising:

- 5 a) a main body having a shape of hollow cylinder and including a tank provided inside of the main body, the tank being capable of containing a wax, the main body being electrically connected by an electric wire;
- b) a chisel tip having a hole, the chisel top being installed at one end of the main body; and
- 10 c) a heating member being heated by a power supply;
- d) wherein the main body includes a plurality of chambers, which are detachably attached to each other, a chisel tip connection portion formed in at least one chamber, and a tube member forming a tube passageway and connecting the tank and the
- 15 chisel tip connection portion.

2. An electric wax chisel according to claim 1, wherein the main body comprises: a) a first chamber having a tube member, an exit hole being formed at one end of the tube member and an

20 inlet hole being formed at the other end of the tube member, the exit hole being connected with the tip connection portion; and b) a second chamber having a discharging hole to be connected with the inlet hole of the first chamber, a tank to contain a wax being provided inside thereof.

25

3. An electric wax chisel according to claim 2, wherein the heating member is disposed either at the side of the exit hole of the first chamber, or at the side of the discharging hole in the second chamber.

30

4. An electric wax chisel according to claim 2, wherein a

filter is disposed selectively at least one of at the exit hole, at the inlet hole, in the tube passageway of the discharging hole, and at a bottom portion of the tank, thereby filtering undesired materials contained in the wax.

5

5. An electric wax chisel according to claim 2, wherein a valve is provided in the tube passageway between the exit hole and the inlet hole in order to selectively open or close the tube passageway by means of the operation of the operating
10 button.

6. An electric wax chisel according to claim 5, wherein the valve includes a solenoid valve electrically connected with the operating button.

15

7. An electric wax chisel according to claim 2, wherein a second valve is further provided in at least one of the inlet hole and the discharging hole in order to prevent the molten wax from releasing through the inlet hole or the discharging hole
20 when the first and second chambers are disassembled.

8. An electric wax chisel according to claim 7, wherein the second valve comprises: a) at least two projections formed in the inner face of the discharging hole along the inner
25 circumference thereof; b) a resilient member disposed at the side of the discharging hole towards of the projections and the inlet holes; and c) an operating member having at one side a flange supported by the resilient member and at the other side an operating pin extending from the center of the flange toward
30 the inlet hole along the axis of the tube member, wherein the operating pin is extended into the inlet hole and one end

portion thereof is supported by the filter.

9. An electric wax chisel according to claim 2, wherein the first chamber is provided with a temperature-sensing device for sensing the temperature of the heating member and intermitting the power supply.

10. An electric wax chisel comprising:

a) a main body having a shape of hollow cylinder and a tank provided inside the hollow cylinder, the tank being capable of containing a wax;

b) a chisel tip mounted at one end portion of the main body; and

c) a heating member heated by a power supply, the heating member being electrically connected by an electric wire of the electric wax chisel;

d) wherein a chisel tip connection portion is integrally formed with the main body, the tank is mounted inside the integral main body, a tube member constituting a tube passageway and connecting the chisel tip connection portion and the tank.

11. An electric wax chisel according to claim 10, wherein the heating member is selectively disposed at least at one position along the length of the tube member.

12. An electric wax chisel according to claim 10, wherein the heating member is disposed in the tank side and chisel tip side respectively of the tube member.

13. An electric wax chisel according to claim 10, wherein a filter for filtering undesired materials contained in the wax is

provided at least one of at the tube member, at one side of the exit hole, and at the bottom portion of the tank.

14. An electric wax chisel according to claim 10, wherein
5 the tube member is provided with a valve for selectively opening or closing the tube passageway by operation of the operating button.

15. An electric wax chisel according to claim 10, wherein
10 the valve includes a solenoid valve electrically connected with the operating button.

16. An electric wax chisel according to claim 10, wherein a
15 temperature-sensing device is provided near the exit hole in the tube passageway of the tube member in order to sense the temperature and intermit the power supply.

17. An electric wax chisel comprising:

a) a main body having a shape of hollow cylinder and a tank
20 provided inside the hollow cylinder, the tank being capable of containing a wax;

b) a chisel tip mounted at one end portion of the main body; and

c) a heating member heated by a power supply, the heating
25 member being electrically connected by an electric wire of the electric wax chisel;

d) wherein an operating button is provided at the outer face of the main body, a control unit to be controlled by the operating button is provided at the inner face of the main body,
30 and a solenoid valve is mounted between the chisel tip and the tank such that one side thereof forms a tube passageway with the

chisel tip and other side thereof forms a tube passageway with the exit hole of the tank and the solenoid valve is controlled by the control of the control unit according to the operation of the operating button.

5

18. An electric wax chisel according to claim 17, wherein the main body is provided with a cap at the other end thereof, the cap having an air control valve, and the tank is able to be disassembled together with the cap.

10

19. An electric wax chisel according to claim 18, wherein the tank is able to be disassembled from the cap and the solenoid valve at one end and the other end thereof respectively, a filter for filtering undesired materials is disposed at the other end, i.e., at the exit hole side, and a consumable wax for a single use is contained inside the tank.

15

20. An electric wax chisel according to claim 17, wherein the heating member is disposed at least one of in the chisel tip, in the solenoid valve, and at the exit hole side of the tank.

20